

EBOX-33xxMX Series, VGA, 24-bit GPIO

Model Type	3300MX-G	3300MX-GC22	3300MX-GC85	3300MX-JSK	
	3310MX-G	3310MX-GC22	3310MX-GC85	3310MX-JSK	
Processor	Vortex86MX for 3300MX Series/ Vortex86MX+ for 3310MX Series (933MHz)				
BIOS	AMI BIOS				
Memory	Onboard 512MB DDR2 for 3300MX Series/ Onboard 1GB DDR2 for 3310MX Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin				
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
Audio	N/A				
GPIO	24-bit GPIO				
I/O	SD Slot	1x			
	SATA	N/A	N/A	N/A	1x
	PS2	PS/2 for Keyboard/ Mouse x 1			
	RS-232	N/A	2x	2x	3x
	RS-422	N/A	1x	N/A	N/A
	RS-485	N/A	N/A	1x	N/A
Auto Power On	Yes				
Power	DC +8V ~ +15V				
Dimensions	115 x 115 x 35 mm				
Unit Net Weight	500g				
Operation Temp.	5 ~ 50 °C				
Certifications	CE, FCC, VCCI				
Note	COM1 (Full 9pin RS-232), COM2 with Y cable extended to COM3 & COM4 (Support TX & RX signals only)				

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86MX/ Vortex86MX+ (933MHz)
- Onboard 512MB/ 1GB DDR2
- PXE Diskless Boot
- 2.5" SATA HDD support (Optional)
- SATA DOM support (Optional)
- SD, SDHC support
- GPIO support
- WiFi Dongle support (Optional)
- USB V2.0 port x 3
- RS-232 Up to 3 ports (Optional)
- RS-485 port x 1 (Optional)
- RS-422 port x 1 (Optional)
- Auto Power On support
- Ultra low power

