

EBOX-3330 Series, VGA, LAN x 2, RS-485

Model Type	EB-3330-L2 851	EB-3330-L2 852	EB-3330-L2 851C1	EB-3330-L2 851C2	EB-3330-L2 851C3	EB-3330-L2 852C1	EB-3330-L2 852C2	EB -3330-L2 851221	3330-L2 851221C1	3330-L2 851221C2	
Processor	Vortex86DX2 (933MHz)										
BIOS	AMI BIOS										
Memory	Onboard 1GB DDR2										
VGA	Integrated Graphics Chip/ D-Sub 15-pin										
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)										
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port										
HD Audio	Line out										
I/O	SD Slot	1x									
	SATA	1x									
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232
COM4	N/A	N/A	N/A	RS-232	N/A	RS-232	N/A	N/A		RS-232	
Auto Power On	Yes										
Power	DC +8V ~ +15V										
Dimensions	115 x 115 x 35 mm										
Unit Net Weight	510g										
Operation Temp.	5 ~ 50 °C										
Certifications	CE, FCC, VCCI										
Optional	1. Mic input 2. 2GB DDR2 onboard 3. Internal SD Card slot 4. TTL Level RS-232										
Note	RS-232 COM ports in Full 9pin										

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86DX2 (933MHz)
- Onboard 1GB DDR2
- PXE Diskless Boot
- 2.5" SATA HDD support
- SATA DOM support
- SD, SDHC support
- WiFi Dongle support (Optional)
- 3 x USB V2.0 ports (2 at the front)
- 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- RS-232 Up to 3 ports (Optional)
- RS-485 Up to 2 ports (Optional)
- RS-422 x 1 port (Optional)
- Ultra low power



DMP Electronics Inc.

No. 15, Wugong 5th Rd., New Taipei Industrial Park, New Taipei City 24890, Taiwan R.O.C

Tel: +886 2 2298 0770 Fax: +886 2 8990 1629