


USB to 2-Port RS-232 DB9 Serial Interface Adapter

sealevel.com/product/2201-usb-to-2-port-rs-232-db9-serial-interface-adapter



DB9M Connector



RS232 Pin Out


Pin #	Signal
1	DCD
2	RX
3	TX
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

Part: 2201 **Model:** SeaLINK+2/232

Rated **5.00** out of 5 based on 1 customer rating
([1 customer review](#))

\$138.00

DB9M RS-232 Loopback



Need some help? [Contact us](#)

Description

The SeaLINK® 2201 USB serial I/O adapter provides two RS-232 serial ports for USB connectivity to legacy or non-USB compliant devices. The 2201 supports standard PC data rates up to 460.8K bps.

Sealevel's [SeaCOM](#) USB software drivers and utilities make installation and operation easy using Microsoft Windows operating systems. After installing the software, simply connect the 2201 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.

Do you know that adapter design can impact your application? Find out how in this [USB Serial performance](#) report.

Category: [Two Port](#)

Additional information

Family	SeaLINK
Communications Chip	USB/UART
Dimensions	7.1 (L) x 5.3 (W) x 1.5 (H)
Electrical Interface	RS-232
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	50 feet
Max Data Rate	460.8K bps
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	2
Power Requirement	+5V @ 500mA
RoHS Compliant	Yes

Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Powered	Yes
USB Specification	1.1 Compliant2.0 Compatible

Compliant with RoHS and WEEE directives

High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO

Data rates to 460.8K bps

All modem control signals implemented

Serial and USB activity LEDs

Hot-swappable

Powered by USB connection

Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems

DB-9M connectors

Includes 6' USB device cable (Item# [CA179](#))

Copyright 1996 - 2023 - Sealevel Systems, Inc. All rights reserved.