

# Linux-based Arm9 Programmable Automation Controller

# PAC-5010



## Features

- Linux kernel 2.6.14 OS with file system
- 64MB SDRAM and 16MB NOR Flash
- 16 x opto-isolated digital inputs
- 8 x Darlington-pair digital outputs to drive external relays
- 2 x 10/100Mbps Ethernet ports
- 1 x RS-232 port, 1 x RS-485 port
- 2 x USB 2.0 host ports for add-on functionality expansion
- 1 x SD memory card slot included for storage expansion
- GNU C / C++ toolchain for Linux / Windows environment
- 9~40VDC input range

## ■ H/W Specifications

### CPU / Memory

- CPU: ATMEL Arm9 AT91RM9200 180MHz w/MMU
- Memory: 64MB SDRAM, 16MB NOR Flash

### Network Interface

- Type: 2 x 10/100BaseT, RJ45 connector

### TTY (Serial) Ports

- RS-485: One port, with screw-fixed wiring terminal  
Signals: Data+, Data-, GND
- RS-232: One port, with 10-pin header  
Signals: Tx, Rx, RTS, CTS, DSR, DTR, DCD, GND
- Console: One port, with 10-pin header  
Signals: Tx, Rx, GND

### TTY (Serial) Port Parameters

- Baud Rate: Up to 921.6Kbps
- Parity: None, Even, Odd, Mark, Space
- Data Bits: 5, 6, 7, 8
- Stop Bits: 1, 1.5, 2
- Flow Control: RTS / CTS, XON / XOFF, None

### USB Ports

- Host Ports: 2, USB 2.0 compliant, with 10-pin header
- Data Rate: Up to 12Mbps

### Mass Storage

- 1 x Micro-SD socket (at bottom side)
- SD 2.0 Compliant, support SDHC

### Isolated Digital Input

- No. of Channels: 16
- Logical High: 5~24VDC
- Logical Low: 0~1.5VDC
- Input Resistance: 1.2K ohms@0.5W
- Response Time: 20µs
- Opto-isolation: 2500Vrms

### Digital Output

- No. of Channels: 8
- Source Driver: UDN2981A (Allegro MicroSystems)
- Source Voltage (VDD): 5~50VDC
- Output Current: 500mA max.

### General

- Watchdog Timer: Yes, for kernel use
- Real-Time Clock (RTC): Yes
- Buzzer: Yes
- Power Input: +9~+40VDC
- Power Consumption: 12VDC@800mA
- Dimensions (W x H x D): 160 x 104 x 32mm (6.3x4.13x1.26in)
- Operating Temperature: 0~70°C (32~158°F)
- Regulation: CE Class A, FCC Class A

## ■ S/W Specifications

### General

- OS: Linux, kernel 2.6.14
- Boot Loader: U-Boot
- File Systems: JFFS2, ETX2 / ETX3, VFAT / FAT, NFS

### Protocol Stacks

- IPv4, ICMP, ARP, DHCP, NTP, TCP, UDP, FTP, TELNET, HTTP, PPP, PPPoE, CHAP, PAP, SMTP, SNMP V1 / V2, SSL, SSH 1.0 / 2.0

### Pre-installed Utilities

- bash: shell command
- tinylogin: login and user manager utility
- telnet: telnet client program
- busybox: Linux utility collection
- ftp: ftp client program

### Daemons

- pppd: dial in / out over serial port and PPPoE
- snmpd: SNMP agent program
- telnetd: telnet server program
- inetd: TCP server program
- ftpd: ftp server program
- boa: web server program
- sshd: secured shell server
- iptables: firewall service manager
- amgrd: Artila manager daemon

### Toolchain for Linux

- GCC: C / C++ PC cross compiler for Linux, Cygwin
- GLIBC: POSIX Library

### Device Drivers

- SD / MMC, UART, Real Time Clock, Buzzer, Digital I/O, Ethernet, Watchdog Timer

### USB Host Drivers (Could Be Customized)

- Flash disk
- WiFi (IEEE-802.11)
- RS-232 adapters

## ■ Ordering Information

### PAC-5010

- Linux-based Arm9 Programmable Automation Controller

### CB-F10M9-20 (91-0P9M9-001)

- Console Cable (10Pin Header to DB9 Male, 20cm)



Authorized Distributor

[wdsystems.com](http://wdsystems.com)

[sales@wdsystems.com](mailto:sales@wdsystems.com)

800-548-2319

919-545-2500

220 Chatham Business Drive  
Pittsboro, NC 27312