

DDR4 WT (wide temperature) SODIMM offers a compact design and the industry's fastest memory speed with 3200MT/s - the perfect fit for any in-vehicle, surveillance, automation and embedded application. The modules comply with all relevant JEDEC standards, can operate in temperatures from -40°C to 85°C, and are available in 4GB, 8GB, 16GB, and 32GB capacities. 2133MT/s, 2400MT/s and 2666MT/s modules are also available.

Specifications:

Interface	DDR4
Form Factor	WT SODIMM
Data Rate	2133 MT/s, 2400 MT/s, 2666 MT/s, 3200 MT/s
Capacity	4GB, 8GB, 16GB, 32GB
Function	Non-ECC Unbuffered Memory
Pin Number	260pin
Width	64Bits
Voltage	1.2V
PCB Height	1.18 Inches
Operating Temperature	-40°C to 85°C
30μ" Gold Finger	Y
Anti-Sulfuration	Y

Order Information:

Density	Component composition	Part Number	Rank	Voltage	Description
4GB	512Mx8	M4S0-4GSSN5EM	1Rx8	1.2V	DDR4 3200 WT SODIMM
4GB	512Mx16	M4S0-4GSXZ5EM	1Rx16	1.2V	DDR4 3200 WT SODIMM
4GB	512Mx16	M4S0-4GMXZ5EM	1Rx16	1.2V	DDR4 3200 WT SODIMM
8GB	512Mx8	M4S0-8GSSO5EM	2Rx8	1.2V	DDR4 3200 WT SODIMM
8GB	1Gx8	M4S0-8GS1N5EM	1Rx8	1.2V	DDR4 3200 WT SODIMM
8GB	1Gx8	M4S0-8GM1N5EM	1Rx8	1.2V	DDR4 3200 WT SODIMM
8GB	1Gx16	M4S0-8GSYZ5EM	2Rx16	1.2V	DDR4 3200 WT SODIMM
16GB	1Gx8	M4S0-AGS1O5EM	2Rx8	1.2V	DDR4 3200 WT SODIMM
16GB	1Gx8	M4S0-AGM1O5EM	2Rx8	1.2V	DDR4 3200 WT SODIMM
16GB	2Gx8	M4S0-AGS2N5EM	1Rx8	1.2V	DDR4 3200 WT SODIMM
16GB	2Gx8	M4S0-AGM2N5EM	1Rx8	1.2V	DDR4 3200 WT SODIMM
32GB	2Gx8	M4S0-BGS2O5EM	2Rx8	1.2V	DDR4 3200 WT SODIMM
32GB	2Gx8	M4S0-BGM2O5EM	2Rx8	1.2V	DDR4 3200 WT SODIMM
4GB	512Mx8	M4S0-4GSSNIEM	1Rx8	1.2V	DDR4 3200 WT SODIMM
8GB	512Mx8	M4S0-8GSSOIEEM	2Rx8	1.2V	DDR4 3200 WT SODIMM
8GB	1Gx8	M4S0-8GS1NIEEM	1Rx8	1.2V	DDR4 3200 WT SODIMM
16GB	1Gx8	M4S0-AGS1OIEEM	2Rx8	1.2V	DDR4 3200 WT SODIMM
32GB	2Gx8	M4S0-BGS2OIEEM	2Rx8	1.2V	DDR4 3200 WT SODIMM



Authorized Distributor

wdsystems.com

sales@wdsystems.com

800-548-2319

919-545-2500

220 Chatham Business Drive
Pittsboro, NC 27312