ADLINK
LEADING EDGE COMPUTING

SBC35-MTL

3.5" Single Board Computer with Intel® Core™ Ultra Processors

Features

- Intel® Core™ Ultra Processor delivers efficient, high-performance computing.
- Integrated NPU enhances AI processing capabilities for real-time applications.
- Reserved MIPI-CSI Signal Pathway for camera Integration.

Windows

Ordering Information

PN	Model Name	CPU	Memory	DP	HDMI	LCD	USB Type-C	LAN	COM	SATA	USB2.0	USB3.0	M.2	SBC-FM	TPM
91-47301-00	SBC35-MTL	125H	2x DDR5 SO-DIMM 5600 MHz	1	1	eDP	1	2	2	1	3	2	3	Support	Support (option)

Packing Lists

PN	Description	QTY
91-47301-00	SBC35-MTL	1
58-10515-0000	M.2 screw kit	1
58-10514-0000	Thermal kit	1

Embedded OS

PN	Description
92-56094-0010	Windows 10 IoT Ent LTSC 2021 High End PKEA
92-56094-2010	Windows 10 IoT Ent LTSC 2021 Value PKEA
92-56094-4010	Windows 10 IoT Ent LTSC 2021 Entry PKEA
92-56101-0010	Windows 11 IoT Ent High End PKEA
92-56101-2010	Windows 11 IoT Ent Value PKEA
92-56101-4010	Windows 11 IoT Ent Entry PKEA

Optional Accessories

PN	Description
32-21014-1000-A0	CPU cooler for 28W CPU
32-21015-1000-A0	Passive Heatsink for 15W CPU
30-21363-0000-A0	USB 2.0 Type A connectorx1
30-22139-2000-A0	RS-232/RS-485/RS-422x2
30-21535-6000-A0	GPIO +Audio +USB 2.0x2
30-22121-0000-A0	SATA+ SATA Power
30-22224-0000-A0	AFM PWR Cable
30-22238-0000-A0	2x2P to DC JACK Cable
91-49076-0010	SBC35-MTL LVDS FPC

Specifications

Model	SBC35-MTL
Processor System	
CPU	MTL-U, 15W /MTL-H, 28W
Memory	2x DDR5 SO-DIMMs 5600MHz, up to 96 GB, non-ECC
OS Support	Win10/ Win11 24H2 LTSC Ubuntu 22.04LTS (support by project)
Display	
VGA	-
HDMI	1x HDMI2.0
DisplayPort	1x DP1.4
LVDS/ eDP	eDP x1 (LVDS through RPL driving board)
Type-C	1
Number of Displays	4 (HDMI, DP, Type-C, LVDS/eDP)
Ethernet	
Gbe Port	2
Controller/ Frequency	2x Intel® I226V, 2.5Gps / 1Gbps/ 100Mbps / 10Mbps
I/O Interfaces	
USB	2x USB 3.2 Gen 2x1 ports (10Gbps) (rear I/O) 2x USB 2.0 through 30pin header 1x USB 2.0 via headers
USB Type-C	1x USB TYPE-C (USB 3.2, DP, Power delivery 5V, 3A)
COM	2x RS-232/422/485 pin headers
Serial ATA	1x SATA 6Gb/s ports w/ 5V SATA power
Audio	Realtek ALC888S 1x line-in, 1x line-out, MIC-in through 30pin header
Expansion Slots	1x M.2 2280 M Key (PCIex4) 1x M.2 2230 E Key (PCIe Gen 4x1, USB) 1x M.2 3042 B-key (USB3.0/2.0, PCIex1) w/ SIM card
TPM	TPM2.0 (option)
DI/ DO	GPIO 8-bit through 30pin header
FM board expansion	
PCIex1	1
PCIex4	1 (up to Gen3)
USB 3.0/2.0	1
LPC	-
eSPI	1
Mechanical and Environmental	
Dimension	5.75" x 4" (146mm x 102mm)
Operating Temperature	0 to 60 °C
Storage Temperature	-40°C to 85°C
Power Supply	12V-24V connector type: 2x2 connector + DC JACK co-lay
ESD	Contact +/-8 KV, Air +/-12 KV
Certification	
	CE & FCC Class B

Product Illustration



Block Diagram



*Default by BOM change, contact with your local sales to support option.

All products and company names listed are trademarks or trade names of their respective companies. Updated Jan. 15, 2025. ©2025 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.

Authorized Distributor

wdlsystems.com

sales@wdlsystems.com

800-548-2319

919-545-2500

220 Chatham Business Drive
Pittsboro, NC 27312