



DMP Electronics Inc.

8F, No 12, Wu-Quan 7 Rd., Wu Gu Industrial Park
Wu Gu Xiang, Taipei 248, Taiwan R.O.C.
TEL: 886 2 2298 0770 FAX: 886 2 2290 2335

DMP unveil Green Compact PC eBox-3300 (Only 10W)




Nov. 2008 - DMP Electronics Inc., launched the very first energy saving eBox-3300, this 10W computer use the latest MSTI PDX-600 CPU has Ultra low power consumption, mini size, high performance and fanless etc., advantages for environment.

「The globe warming is the most concern issue recent years. DMP treat this issue as the priority event for globe villages, therefore DMP spend years researching and developing for the products which can save the energy and reduce the carbon dioxide, for satisfying the consumer's expectation of environment protection of the IT products.

The eBox-3300 only consumes 10W power with a palm size dimension. The power consumption is only 1/30 compare with the normal Desktop and 1/8 compare with the normal laptop. Compare with traditional 300W Desktop you can save more power fee every single month.

The feature of eBox-3300 10W is not only low power consumption but also in a small dimension, the 115x115mm form factor design is only 1/10 volume of the normal Desktop. It can save a lot of room for enterprise and personal using. This system use MSTI PDX-600 CPU with the 256MB DDR2, let the system can run the Windows series and Linux O/S. the chassis support the VESA mounting hole. It can be easily mounted in the back of LCD monitor which supporting the VESA mounting hole. You don't need to worry about the life cycle of the fan anymore because the eBox-3300 is fanless design. There will be no dust gathered inside your computer anymore. The really extend the life cycle of the computer.





DMP Electronics Inc.

8F, No 12, Wu-Quan 7 Rd., Wu Gu Industrial Park
Wu Gu Xiang, Taipei 248, Taiwan R.O.C.
TEL: 886 2 2298 0770 FAX: 886 2 2290 2335

Specification

Model	eBox-3300
CPU	MSTI PDX-600 (1GHz)
Memory	Onboard 256MB DDR2
VGA	XGI Z9s with 32MB DDR2 External 15-pin D-type female VGA connector
Ethernet	Integrated 10/100 Mbps LAN Built-in PXE diskless boot function
2 nd Ethernet	Realtek RTL8100B 10/100Mbps Ethernet (optional)
I/O	44pin IDE box header x 1 Micro SD socket x 1 (bootable) CF Slot x 1 (bootable) USB V2.0 x 3 (2 in the front) RJ-45 x 1 PS2 for Keyboard/Mouse x 1 Mini PCI Socket x 1 (optional) RS-232 port x 2 (optional)
Audio	Mic in and Line out
Power	+5V @ 2A (10 W)
Dimensions	115 x 115 x 35 mm
Weight	505g

Note: The specification is subject to change without prior notice.

Ordering Information:

eBox-3300: Standard Version

eBox-3300-H: Standard Version with support for 2.5" HDD

eBox-3300-M: Standard Version with Mini PCI Socket

eBox-3300-JSK: Standard Version with Mini PCI Socket and 2 x RS-232

eBox-3300-L2: Standard Version with two LAN and 2 xRS-232 but No P/S2

eBox-3300-LS: Standard Version with Linux O/S and support RDP. ICA. VNC. XDMCP